

# Reflex Reflex DD 8, flow through expansion vessel, green, 25/4 bar

Article number: 7290200

**reflex**

Thinking solutions.



## Features

Type	DD 8
Colour	green
Diaphragm material	butyl
Nominal volume	8 l
Max. useful volume	6 l
Max. permissible system temperature	70 °C
Min. perm. operating temperature	-10 °C
Max. perm. operating temperature	70 °C
Max. perm. operating pressure	25 bar
Factory provided gas supply pressure	4 bar
Connection	G 3/4"
Diameter	206 mm
Height	344 mm
Tilt dimension approx.	401 mm
Weight	3,45 kg

## Description

### Reflex Reflex DD 8

Flowed through diaphragm expansion tank for DHW systems, water supply installations and pressure-boosting systems. With diaphragm according to the elastomer directive and W 270. Exterior and interior coating in compliance with KTW-A. Only suitable for cold water systems. The flow is implemented using a high-flow circulation star and the enclosed 3/4" T-piece

Vessels fitted according to DIN EN 13831. Checked according to DIN 4807 part 5. Vessels with a permissible operating pressure of 10/16 bar with DIN DVGW Reg. no. NW-0411AT2534. Approval according to Pressure Equipment Directive 2014/68/EU

- Circulation with high-flow circulation star
- Parts in contact with water are corrosion-protected
- Non-replaceable bladder according to DIN EN 13831 DIN 4807 T5, KTW-C and W270
- Interior and exterior coating in compliance with KTW-A
- May be combined with the Flowjet—flow through valve
- 33 litres with brackets
- Only for use in cold water pipes (consider installation and operating instructions)

