

BALL VALVES



BALL VALVE

Ball valve for heating and cooling systems. Available in the pressure classes PN 40 and PN 30.

BAV 86

SHUT-OFF VALVES

TECHNICAL DESCRIPTION

Applications:

Heating and cooling systems

Function:

Shut-off

Dimensions:

DN 15-50

Pressure class:

PN 40 (DN 15-25)

PN 30 (DN 32-50)

Temperature:

Max. working temperature: 120°C

Min. working temperature: 0°C

Material:

Body: Brass DZR CuZn36Pb2As EN 12165

Spindle: Brass DZR CuZn36Pb2As EN 12165

Ball: Brass DZR CuZn36Pb2As EN 12165 (chromed)

Seal: PTFE

Spindle seal springs: EPDM O-ring

Lever: Iron, coated with zinc and plastified

Marking:

TA-SC, PN, DN and year of production.

Colour:

Handle: Red


Approvals:

WRAS



Female threads

Threads according to ISO 228



TA No	DN	D	L1	L2	H	Kg
PN 40						
78 620-015	15	G1/2	58,5	92	41	0,20
78 620-020	20	G3/4	67,5	92	46	0,30
78 620-025	25	G1	80	120	55,5	0,49
PN 30						
78 620-032	32	G1 1/4	96	120	63	0,76
78 620-040	40	G1 1/2	106	150	80	1,1
78 620-050	50	G2	130	150	88	1,9

Tour & Andersson retains the right to make changes to its products and specifications without prior notice.

2-60-5 BAV 86 2008.04

TA-SC[®]