

CHECK VALVES



SWING CHECK VALVE

Swing check valve for heating and cooling systems. Available in pressure class PN 16.

NRV 27

ADDITIONAL PRODUCTS

TECHNICAL DESCRIPTION

Applications:

Heating and cooling systems

Function:

Unidirectional flow

Dimensions:

DN 15-50

Pressure class:

PN 16

Temperature:

Max. working temperature: 95°C

Min. working temperature: 0°C

Material:

Body: Bronze (CuSn5Zn5Pb5-c) CC491K EN 1982:2000

Cap: Brass CuZn40Pb2 EN 12165

Flap: Brass CuZn40Pb2 EN 12165

Seals: NBR (DN 15-25), PTFE (DN 32-50).


Marking:

TA-SC, PN, RG5 and size (inch)



Female threads

Threads according to ISO 228



TA No	DN	D1	D2	L	H	Kg
78 630-015	15	G1/2	14	55	36	0,20
78 630-020	20	G3/4	20	62	43	0,34
78 630-025	25	G1	25	72	49	0,48
78 630-032	32	G1 1/4	30	82	57	0,69
78 630-040	40	G1 1/2	35	90	63	0,90
78 630-050	50	G2	47	105	69	1,3

Tour & Andersson retains the right to make changes to its products and specifications without prior notice.

16-10-5 NRV 27 2008.04

TA-SC®